

- Draws same current as a 21 watt globe
- Shock, dust & water proof
- 5 Year warranty



DUMMY LOAD RESISTORS



Part Number

LR12/2 - 12 Volt, Blister twin pack
50 Watt 6Ω ohms



Part Number

LR24/2 - 24 Volt, Blister twin pack
50 Watt 24Ω ohms

Must be mounted on metal surface, the resistor can reach temperatures of up to 170° Celsius You may require up to 1 resistor per function on each side.

Dummy load resistors designed to draw the same current as a 21 watt globe. They can be used on vehicles that have electronic components that are not LED compatible.

The Resistor should ALWAYS be wired between the input wires of the lamp, NOT the chassis of the vehicle or trailer! If fitted to the Chassis, a bad earth connection is possible, and can result in problems with the lighting system of the vehicle!

Indicator Circuit:

If fitting to the indicator circuit, fit one lead of the resistor to the positive supply side (Yellow wire) and the other lead of the resistor to the negative supply or ground input wire (White).

Brake Circuit:

If fitting to the brake circuit, fit one lead of the resistor to the positive supply side (Red Wire) and the other lead of the resistor to the negative supply or ground input wire (White)

Correct Fitting:

To fit the resistor, use the crimp terminals supplied. Cut the loom and re-connect the cut wires within the supplied crimp terminal with one side of the resistor crimped into that terminal. Repeat the process for the remaining wire and the other end of the resistor.
Use the 2 screw down points on the resistor to secure it to a metal chassis.

Important Notice:

Must be mounted on metal surfaces, the resistor can reach up to 170 deg C, do not mount the resistor on any surface that can be melted by the heat of the resistor, this includes plastics, hoses or painted surfaces.

